

AD-01W-FS

VDSL2 Compliant Sealed Station Protector

CPE/Premise Wiring

MDU

Utility/Municipality



AD-01W-FS

Tii's Angle Driver® AD-01W-FS is specifically designed to protect tomorrow's high-speed digital networks, such as ADSL2+/VDSL2 technology against damage caused by electrical surges.

KEY PRODUCT BENEFITS

- ▶ Optimal performance for IPTV video over DSL due to low line to ground capacitance, providing significantly better DSL Insertion Loss than most competitive products
- ▶ AD-01W-FS consists of a heavy duty three-electrode gas tube surge arrester, failshort device and Gel-Sealed IDC (Insulation Displacement Connection) type connectors for terminating all wires in one completely self-contained unit
- ▶ Tii's "11" tube provides unsurpassed lightning protection
- ▶ IDC connections require no stripping of the wire insulation for terminating
- ▶ Module has two ports for small-gauge (22-26 AWG) wire terminations and two ports designed to accept large-gauge (18-19 AWG) or small-gauge (22-24 AWG) wire for tip/ring connections, all of which are environmentally sealed
- ▶ May be employed in a variety of single and multiple pair Network Interface and station protector housings
- ▶ Can be used to retrofit/service upgrades of existing assemblies already installed in the field
- ▶ Unit is supplied with a unique, universal ground tab which may be snapped off to allow for multiple mounting arrangements

INDUSTRY STANDARDS

- ▶ Fully compatible and exceeds the transmission requirements of Telcordia specification GR-974-CORE for high-speed digital networks
- ▶ Tii Angle Driver® AD-01W-FS complies with the "No back-up device" section of Telcordia GR-1361-CORE and has been fully tested by Telcordia and meets the temperature aging and cycling performed at a modified (increased severity) 150Vdc bias for protectors deployed in DSL applications. The resulting lower capacitance and increased reliability make the protector an excellent choice for Digital Subscriber Line (DSL) applications. It exceeds the transmission requirements for high-speed digital networks
- ▶ Surge handling and life capabilities of the Angle Driver® AD-01W-FS meet the objectives of Telcordia GR-1361-CORE
- ▶ Angle Driver® AD-01W-FS meets the requirements of Section 5, "Environmental Requirements, Severe Climatic Conditions" and Section 6.2 "Environmental, Severe Climatic and Flooded Conditions" of Telcordia GR-49-CORE Issue 2, "Generic Requirements for Outdoor Telephone NIDs"
- ▶ Meets Sealing Requirements of Telcordia TR-NWT-000975
- ▶ Meets Generic Requirements For IDC Cross-Connect & Terminal Blocks of Telcordia TR-NWT-001195
- ▶ Listed to UL 497




Tii Technologies Inc.

Corporate Headquarters:

141 Rodeo Drive
Edgewood, NY 11717
Phone: 631.789.5000
Fax: 631.789.5063
Toll Free: 888.844.4720
sales@tiitech.com

AD-01W-FS



Dimensions are in Inches

SPECIFICATIONS

DC Breakdown Voltage (L-G) @ 2000 V/sec	265-600V DC
Impulse Reset: 135Vdc @200mA	<150 mS
Maximum Single Impulse Discharge Current, 8/20 waveform:	20kA 10kA/Side Simultaneously
Impulse Life:	
10 Amp, 10/1000µsec waveform:	1500 Surges Minimum
100 Amp, 10/1000µsec waveform:	100 Surges Minimum
300 Amp, 10/1000µsec waveform:	50 Surges Minimum
AC Discharge Current	
10 Amp, 1 Second:	20 Operations Minimum
1 Amp, 1 Second:	60 Operations Minimum
Capacitance (L-G)	10 pF Typical
Capacitance Imbalance (L-G)	<1 pF Typical
Aging, Temperature/Humidity Cycling with Surge	150 Volts DC Bias
Insertion Loss 0.2 – 30MHz	<0.1dB
Return Loss @30MHz	>15dB
Impulse Breakdown voltage (L-G) @100V/µsec. 500V Typical, @1KV/µsec.	750V Maximum 750V Typical
Insulation Resistance @50Vdc, 10MA:	100 Megohms Minimum

ORDERING INFORMATION

Model No.	Description
AD-01W-FS	Heavy Duty Total Failsafe® TFS® Gel-Sealed Station Protector With Snap-Off Ground Tab